



■ Räder ab Seite 115

rollgroup®

■ Räder für Schwerlastrollen

Seite 133 - 137



Räder für Schwerlastrollen






■ Spezifikationen
 Rad aus Polyamid
 natur
 Gleitlager
 schwere Ausführung

- Ø 100 – 250 mm
- Rad OTO

600 – 1700 kg



Räder

Bestell-Code	 mm	 kg	 mm	 mm	 mm
OTO 100x50-20	100	600	50	20	60
OTO 125x50-15	125	700	50	15	60
OTO 150x50-20	150	800	50	20	60
OTO 160x50-20	160	850	50	20	60
OTO 200x50-20	200	1200	50	20	60
OTO 200x50-25	200	1200	50	25	60
OTO 250x50-25	250	1200	50	25	60
OTO 250x58-25	250	1700	58	25	75






■ Spezifikationen
 Rad aus Polyamid
 natur
 Präzisionskugellager
 schwere Ausführung

- Ø 100 – 250 mm
- Rad OTP

600 – 1700 kg



Räder

Bestell-Code	 mm	 kg	 mm	 mm	 mm
OTP 100x50-20	100	600	50	20	60
OTP 125x50-20	125	700	50	20	60
OTP 150x50-20	150	800	50	20	60
OTP 160x50-20	160	850	50	20	60
OTP 200x50-20	200	1200	50	20	60
OTP 200x50-25	200	1200	50	25	60
OTP 250x50-25	250	1200	50	25	60
OTP 250x58-25	250	1700	58	25	75






■ Spezifikationen
 Rad aus Polyamid
 natur
 Präzisionskugellager
 superschwere Ausführung

- Ø 80 – 200 mm
- Rad OMP

1000 – 4500 kg



Räder

Bestell-Code	 mm	 kg	 mm	 mm	 mm
OMP 80x40-20	80	1000	40	20	45
OMP 100x40-20	100	1200	40	20	45
OMP 100x55-25	100	1800	55	25	60
OMP 125x55-25	125	2000	55	25	60
OMP 150x55-30	150	2500	55	30	60
OMP 150x80-35	150	3000	80	35	90
OMP 200x55-35	200	3000	55	35	60
OMP 200x80-45	200	4500	80	45	90



Räder für Schwerlastrollen

Spezifikationen
Radkörper aus Guss
Lauffläche aus Polyurethan
Präzisionskugellager

- Ø 100 – 500 mm
- Rad TFP

350 – 3150 kg



Räder

Bestell-Code	mm	kg	mm	mm	mm
TFP 100x 40-20	100	350	40	20	50
TFP 100x 50-20	100	450	50	20	60
TFP 125x 50-20	125	560	50	20	60
TFP 150x 50-20	150	660	50	20	60
TFP 150x 50-25	150	660	50	25	60
TFP 150x 60-20	150	800	60	20	60
TFP 150x 60-25	150	800	60	25	60
TFP 160x 50-20	160	700	50	20	60
TFP 200x 50-20	200	890	50	20	60
TFP 200x 50-25	200	890	50	25	60
TFP 200x 60-20	200	1100	60	20	60
TFP 200x 60-25	200	1100	60	25	60
TFP 200x 75-25	200	1350	75	25	75
TFP 200x 75-30	200	1350	75	30	75
TFP 250x 50-20	250	1050	50	20	60
TFP 250x 50-25	250	1050	50	25	60
TFP 250x 60-25	250	1350	60	25	75
TFP 250x 60-30	250	1350	60	30	75
TFP 250x 75-25	250	1650	75	25	75
TFP 250x 75-30	250	1650	75	30	75
TFP 250x 80-30	250	1800	80	30	85
TFP 250x100-40	250	2100	100	40	140
TFP 300x 60-30	300	1600	60	30	85
TFP 300x 75-30	300	2000	75	30	85
TFP 300x100-40	300	2500	100	40	120
TFP 360x 75-40	360	2200	75	40	90
TFP 400x100-40	400	3100	100	40	120
Stahlschweißkonstruktion:					
TSP 500x85-50	500	3150	85	50	90

Varianten: Auch in Vulkollan lieferbar. Andere Größen und Breiten bis 5200 kg auf Anfrage.

Spezifikationen
Radkörper aus Stahl
Lauffläche aus Elastik-Gummi
Schmiernippel
Präzisionskugellager

- Ø 160 – 250 mm
- Rad EDP

350 – 750 kg



Räder

Bestell-Code	mm	kg	mm	mm	mm
EDP 160x50-20	160	350	50	20	60
EDP 200x50-20	200	450	50	20	60
EDP 200x80-20	200	600	80	20	90
EDP 250x60-20	250	600	60	20	75
EDP 250x80-25	250	750	80	25	90



Räder

Bestell-Code	mm	kg	mm	mm	mm
VFP 200x 75-25	200	500	75	25	90
VFP 250x 80-25	250	675	80	25	85
VFP 300x 85-30	300	800	85	30	90
VFP 360x 60-30	360	750	60	30	75
VFP 360x 85-35	360	1050	85	35	90
VFP 400x 65-35	400	900	65	35	75
VFP 405x130-40	405	1500	130	40	140



Räder

Bestell-Code	mm	kg	mm	mm	mm
VSP 500x 85-40	500	1300	85	40	90
VSP 520x100-40	520	1525	100	40	120
VSP 550x160-50	550	2250	160	50	170
VSP 620x200-50	620	3000	200	50	210



Räder für Schwerlastrollen

■ Spezifikationen

Radkörper aus Stahl, geschweißt lackiert, Vollgummireifen mit Stahldrahtarmierung, Schmier-nippel, Präzisionskugellager






- Ø 200 – 550 mm
- Rad VSP Zwillingssrad



700 – 4500 kg



Räder


Bestell-Code	 mm	 kg	 mm	 mm	 mm
VSP 200x100-25	200	700	2 x 50	25	120
VSP 200x150-25	200	1000	2 x 75	25	160
VSP 250x120-30	250	1100	2 x 60	30	150
VSP 250x150-30	250	1250	2 x 75	30	160
VSP 300x150-30	300	1500	2 x 75	30	180
VSP 300x170-35	300	1600	2 x 85	35	180
VSP 360x150-35	360	1900	2 x 75	35	160
VSP 400x130-40	400	1800	2 x 65	40	140
VSP 500x130-40	500	2200	2 x 65	40	140
VSP 550x320-60	550	4500	2 x 160	60	340



Räder

Bestell-Code	mm	kg	mm	mm	mm
OTP 70x66,0-20	70	450	66,0	20	70,0
OTP 80x69,0-20	80	500	69,0	20	74,0
OTP 82x59,5-20	82	450	59,5	20	59,5
OTP 82x69,0-20	82	500	69,0	20	69,0
OTP 82x78,0-20	82	700	78,0	20	82,0
OTP 82x86,5-20	82	750	86,5	20	86,5
OTP 82x89,0-20	82	750	89,0	20	95,0
OTP 82x91,0-20	82	750	91,0	20	96,0
OTP 82x98,0-20	82	800	98,0	20	100,0

Varianten: Weitere Abmessungen (OTP) auf Anfrage.



Räder

Bestell-Code	mm	kg	mm	mm	mm
TEP 75x 40,0-20	75	280	40,0	20	40,0
TEP 80x 40,0-20	80	290	40,0	20	40,0
TEP 80x 54,0-25	80	390	54,0	25	55,5
TEP 80x 59,5-20	80	440	59,5	20	66,0
TEP 80x 75,0-20	80	550	75,0	20	79,0
TEP 82x 60,0-20	82	450	60,0	20	60,0
TEP 82x 66,0-20	82	480	66,0	20	71,0
TEP 82x 69,0-20	82	500	69,0	20	62,0
TEP 82x 70,0-20	82	520	70,0	20	72,0
TEP 82x 75,0-20	82	570	75,0	20	75,0
TEP 82x100,0-20	82	750	100,0	20	100,0
TEP 85x 60,0-20	85	450	60,0	20	64,8
TEP 85x 70,0-17	85	540	70,0	17	63,0
TEP 85x 75,0-17	85	570	75,0	17	75,0
TEP 85x 80,0-20	85	600	80,0	20	80,0
TEP 85x 90,0-20	85	700	90,0	20	90,0
TEP 85x 95,0-20	85	730	95,0	20	95,0
TEP 85x100,0-20	85	770	100,0	20	100,0
TEP 90x 50,0-20	90	400	50,0	20	50,0

Varianten: Weitere Abmessungen (TEP) auf Anfrage.